



GNF-200 fiber optic sensor P/N: GNF1A

- * Designed to meet GJB150.16A-2009, GJB 150.18A-2009 requirement
- * Lead-Free & Designed to meet RoHS requirement
- * Designed to meet IR 255°C peak Requirement.
- * Vibration: 1 ~ 5.5 Hz, 25.4 mm 5.5 Hz ~ 500 Hz *
- Operating temperature range: -40°C to +65°C



光纤传感器

Communication protocols

1 Data Frame Format: (8 Data Bits, 1 Stop Bit, No Check, Default Rate 9600)

Designator (1byte)	The length of the data (1byte)	Address code (1byte)	Command words (1byte)	Data domains	Checksum (1byte)
77H					

Identifier: Fixed to 0x77.

Data Length: The length from the length of the data to the checksum, including the checksum.

Address Code: The address of the collection module, which is 0x00 by default.

Data field: The content and length of the command word vary accordingly.

Checksum: The sum of the data length, address code, command word, and data field (regardless of carrying).

Note: When the command word or data field changes, the check sum will change. When you change the data field, change the check sum accordingly.



E-NETTR

Note: The data field is a 12-byte return angle value and is divided into three groups, each with a sign bit and three compressed BCD codes. They are the pitch angle, the roll angle, and the azimuth angle. For example: Pitch Angle: +0002.0103°, Roll Angle: -00.5132°, Azimuth: 155.6677°.

77 10 00 01 00 02 01 03 10 00 51 32 01 55 66 77 DD

